

PRODUCT-DETAILS

8161.2

8161.2 - Relay switch for blinds



Ogólne informacje

Extended Product Type	8161.2
ID Produktu	2CLA816120A1001
Numer EAN	8427238016825
Opis katalogowy	8161.2 - Relay switch for blinds
Opis	Rated voltage: 230 V~, +10 % / -10 %
	Rated frequency: 50 Hz
	Suitable for blind, roller blind and awning drives with mechanical or electronic limit switch shut-off.
	With two 230 V multi-way input terminals (Up/Down) for group control.
	With operating mode switch for the following modes: normal, louver, base station, position.
	Wind alarm, cleaning functions can be accommodated via extension input.
	For comfort timer control element 8565.31 or 8565.3
	Remote control also available with blind switches / push-buttons code 8144.X
	Running time: 3 min
	Outputs: 2 Normally open contact
Rated current: 3 A, cos φ0.5	
Rated power: 690 VA	
Control/Signal outputs: 2,	
Temperature range (Device): 0 °C to 35 °C	
Included: fixing claws	

Charakterystyka zamówienia

Numer EAN	8427238016825
Minimalna ilość	1 sztuka

zamówienia

Kod taryfy celnej	85365080
-------------------	----------

Wymiary

Szerokość produktu netto	0.062 m
Wysokość produktu netto	0.073 m
Głębokość produktu netto	0.073 m
Waga produktu netto	0.16 kg

Informacje o pakowaniu

Jednostka opakowania (poziom 1)	1 sztuka
Szerokość opakowania (poziom 1)	0.062 m
Wysokość opakowania (poziom 1)	0.073 m
Długość opakowania (poziom 1)	0.073 m
Waga opakowania brutto (poziom 1)	0.16 kg
EAN opakowania (poziom 1)	8427238016825

Normy środowiskowe

Temperatura powietrza otoczenia	Eksplatacja -5 ... +35 °C Przechowywanie -5 ... +50 °C
---------------------------------	---

Dodatkowe informacje

Stopień ochrony obudowy	IP20
Częstotliwość (f)	50...50 Hz
Rodzaj montażu	Flush mounted (plaster)
Typ produktu	Inserts - Sky platform
Nazwa produktu	Relay switch for blinds
Napięcie znamionowe (U _r)	230 V
ID produktu zastąpionego	2CL0816120
Setting Range	Sun Protection 5000...50000 lx

Certyfikaty i deklaracje (Numer dokumentu)

Arkusze danych, informacja techniczna	9AKK107046A0356
---------------------------------------	-----------------

Klasyfikacje

ETIM 5	EC000044 - Venetian blind switch/-push button
--------	---

ETIM 6	EC000615 - Venetian blind control unit
ETIM 7	EC000615 - Venetian blind control unit
UNSPSC	39122200
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Kategorie

- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Arco → Flush Mounted Inserts → Electronic Switch Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Olas → Flush Mounted Inserts → Electronic Switch Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Sky → Flush Mounted Inserts → Electronic Switch Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Flush Mounted VDE Range - Niessen → Design Tacto → Flush Mounted Inserts → Electronic Switch Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Electronic Push Button → Electronic Push Button - Flush Mounted → Electronic Switch Inserts
- Produkty niskiego napięcia i systemy → Switch Assortments → Light / LoadControl → Movement Detectors → Movement Detectors - Flush Mounted → Electronic Switch Inserts

