

PRODUCT-DETAILS

8185

8185 - USB charger 1.500mA, 2 outlets



General Information	
Extended Product Type	818
Product ID	2CLA818500A100
EAN	8427238107103
Catalog Description	8185 - USB charger 1.500mA, 2 outlet:
Long Description	Input voltage: 100 - 240 Vac ±10%; 50/60 H: Input current: 0,20 A (with maximum load) Output voltage: 5 Vdc ±5% Output current: 1.500 mA (total for both gangs Power consumption in stand-by: <= 0,3W@230Vac Energy efficiency: >= 71% Operating temperature: 02C to 35%
	Without fixing claws Cover plate code: 8585, 8685, 8485, 8285 & 558!

Ordering	
EAN	8427238107103
Minimum Order Quantity	1 piece
Customs Tariff Number	85043180
Dimensions	
Product Net Width	0.073 m
Product Net Width Product Net Height	0.073 m 0.052 m

8185

Length

Product Net Weight	0.069 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	0.073 m
Package Level 1 Height	0.052 m
Package Level 1 Depth / Length	0.073 m
Package Level 1 Gross Weight	0.073 kg
Package Level 1 EAN	8427238107103

Environmental	
Ambient Air	Operation -5 +35 °C
Temperature	Storage -5 +50 °C

Additional Information	
Frequency (f)	5060 Hz
Mounting Type	Flush mounted (plaster)
Number of Outputs	2
Operational Voltage	100240 V
Output Current Maximum (I _{out})	1500 mA
Output Voltage (U _{out})	5 V
Product Main Type	Inserts - Sky platform
Product Name	USB charger 1.500mA, 2 outlets
Replaced Product ID (OLD)	2CL0818500

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	9AKK107046A0356
Instructions and Manuals	2CLX228519N1001

Classifications	
ETIM 5	EC000018 - Insert/cover for communication technology
ETIM 6	EC002949 - USB power supply
ETIM 7	EC002949 - USB power supply
UNSPSC	39121406
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

8185

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Charging\ Devices \rightarrow Cha$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Arco \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Olas \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Sky \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

 $Low\ Voltage\ Products\ and\ Systems \rightarrow Switch\ Assortments \rightarrow Flush\ Mounted\ VDE\ Range\ -\ Niessen \rightarrow Design\ Tacto \rightarrow Flush\ Mounted\ Inserts \rightarrow Charging\ Device\ Inserts$

