

PRODUCT-DETAILS

B23 313-100

Active Energy Class ±1% (or B for MID meters). Reactive Energy Class ±2%.;



General	Informa	ition

Extended Product Type	B23 313-100
Product ID	2CMA100170R1000
ABB Type Designation	B23 313-100
EAN	7392696001700
0.11 5 1.11	

Catalog Description

Active Energy Class ±1% (or B for MID meters). Reactive Energy Class ±2%.;

Long Description

Advanced compact DIN-rail meter with an easy to read back lighted display. The meter is intended for use in the commercial or residential buildings etc. The meter can be used in 3 or 4 wire systems. The meter has several instrumentation values, 25 possible alarms and event logs. Three phase direct connected for active and reactive energy. Import and export of energy in different registers and one total. Resettable register for intermediate values. Up to four tariffs. Two outputs and inputs for pulses or alarm etc. M-Bus communication Accuracy class 1.0 (or 8 for MID meters). The meters is IFC approved +

communication.Accuracy class 1.0 (or B for MID meters). The meters is IEC approved + MID approved and verified.

Ordering	
E-Number (Finland)	6625039
E-Number (Sweden)	0900043
EAN	7392696001700
Minimum Order Quantity	1 piece
Customs Tariff Number	90283019

Dimensions	
Product Net Width	70 mm
Product Net Height	26.5 mm
Product Net Depth / Length	65 mm
Product Net Weight	0.35 kg

Container Information	
Package Level 1 Units	box 1 piece
Package Level 1 Width	100 mm
Package Level 1 Height	68 mm
Package Level 1 Depth / Length	94 mm
Package Level 1 Gross Weight	0.43 kg
Package Level 1 EAN	7392696001700

Environmental	
Ambient Air Temperature	Operation -40 +70 °C
RoHS Status	Following EU Directive 2002/95/EC August 18, 2005 and amendment

Additional Information	
Accuracy	Active Energy Class ±1% (or B for MID meters). Reactive Energy Class ±2%.
Communication Interface	M-bus
Communication	M-Bus TP
Connecting Capacity Main Circuit	1 25 mm²
Current Rating	65 A
Degree of Protection	IP20
Enclosure Material	Plastic
Frequency (f)	50/60 Hz
Function	Electricity meter
Meter Type	Direct connected
Mounting Type	DIN rail
Number of Phases	3
	0.721 W
Product Main Type	B23
Product Name	B23 313-100
Rated Current (I _n)	65 A
Rated Voltage (U _r)	(Un) N-L 220 240 V (Un) L-L 380 415 V
RoHS Date	2012-36
Standards	EN 50470-1
Sub-Function	Silver

RoHS Information

2CMC485006

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	2CMC485003M0201
Declaration of Conformity - CE	2CMC485001D0001
Environmental Information	2CMC485003D0001
Instructions and Manuals	2CMC485019M0201

Classifications	
ETIM 4	EC001506 - Electronic kilowatt-hour meter
ETIM 5	EC001506 - Kilowatt-hour meter
ETIM 6	EC001506 - Kilowatt-hour meter
ETIM 7	EC001506 - Kilowatt-hour meter
Object Classification Code	P
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)

Categories

 $Low\ Voltage\ Products\ and\ Systems\ \rightarrow\ Modular\ DIN\ Rail\ Products\ \rightarrow\ Energy\ Efficiency\ Devices\ \rightarrow\ Energy\ Meters$

