

PRODUCT-DETAILS

CLV332-4

Industrial Connectors, 3P, 32 A, 25 and 50 AC V



General Information

Extended Product Type	CLV332-4
Product ID	2CMA100912R1000
EAN	7392696009126
Catalog Description	Industrial Connectors, 3P, 32 A, 25 and 50 AC V
Long Description	Connector Extra low voltage, secondary key position 4h, rated current 32A, IP44 splashproof, 3-poles, frequency 100-200 Hz, color code Green

Ordering

E-Number (Sweden)	E2417748
EAN	7392696009126
Country of Origin	Austria (AT)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	75 mm
Product Net Weight	0.198 kg

Container Information

Package Level 1 Width	152 mm
Package Level 1 Depth / Length	152 mm
Package Level 1 Height	77 mm
Package Level 1 Gross Weight	1.98 kg
Package Level 1 EAN	7392696009607
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 10 mm²
Cable Diameter	8 ... 24 mm
Cable Entry Position	Swivel
Color	Green
Connection Type	Screw
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Extra low voltage connector
Housing Material	Plastic
Invoice Description	Ind. P_S#CLV332-4
Number of Poles	3
Order Multiple	10 piece
Product Main Type	CLV
Product Name	Extra low voltage connector
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Voltage (U_r)	20 ... 25 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 7001 - Silver Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage

