

## PRODUCT-DETAILS

# RSLV316-12

## Industrial Socket Outlets for Surface Mounting, 3P, 16 A, 40 ... 50 AC V



### General Information

|                       |                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | RSLV316-12                                                                                                                                                           |
| Product ID            | 2CMA100989R1000                                                                                                                                                      |
| EAN                   | 7392696009898                                                                                                                                                        |
| Catalog Description   | Industrial Socket Outlets for Surface Mounting, 3P, 16 A, 40 ... 50 AC V                                                                                             |
| Long Description      | Socket Outlet Extra low voltage for surface mounting, secondary key position 12h, rated current 16A, IP44 splashproof, 3-poles, frequency 50-60 Hz, color code White |

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Sweden)      | E2417759      |
| EAN                    | 7392696009898 |
| Country of Origin      | Austria (AT)  |
| Minimum Order Quantity | 10 piece      |

### Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 71 mm    |
| Product Net Height | 85 mm    |
| Product Net Weight | 0.215 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 121 mm        |
| Package Level 1 Depth / Length | 121 mm        |
| Package Level 1 Height         | 87 mm         |
| Package Level 1 Gross Weight   | 2.15 kg       |
| Package Level 1 EAN            | 7392696010139 |
| Package Level 1 Units          | box 10 piece  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000072M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                       |
|----------------------------|---------------------------------------|
| Additional Information     | 3P                                    |
| Ambient Temperature        | -25 ... 40 °C                         |
| Cable Cross-Section        | 1 ... 10 mm <sup>2</sup>              |
| Cable Diameter             | 8 ... 24 mm                           |
| Color                      | White                                 |
| Connection Type            | Screw                                 |
| Degree of Protection       | IP44                                  |
| Function                   | Extra low voltage wall mounted socket |
| Housing Material           | Plastic                               |
| Invoice Description        | Ind. P_S#RSLV316-12                   |
| Number of Poles            | 3                                     |
| Order Multiple             | 10 piece                              |
| Product Main Type          | RSLV                                  |
| Product Name               | Extra low voltage wall mounted socket |
| Protection Type            | Splashproof                           |
| Rated Current ( $I_n$ )    | 16 A                                  |
| Rated Voltage ( $U_r$ )    | 40 ... 50 V AC                        |
| Standards                  | IEC 60309-1, -2                       |
| Suitable for Product Class | IEC Industrial Plugs and Sockets      |
| Instructions and Manuals   | 2CMC700014C0016                       |
| RAL Number                 | RAL 7001 - Silver Grey                |

| Classifications |          |
|-----------------|----------|
| eClass          | 27440510 |
| UNSPSC          | 39120000 |

| Categories                                                                                                                        |
|-----------------------------------------------------------------------------------------------------------------------------------|
| Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage |

