


## PRODUCT-DETAILS

# BSLV216

## BSLV216 Industrial Inlets for Surface Mounting, 2P, 16 A, 20 ... 25 V



### General Information

|                       |                                                                                                                                           |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | BSLV216                                                                                                                                   |
| Product ID            | 2CMA100991R1000                                                                                                                           |
| EAN                   | 7392696009911                                                                                                                             |
| Catalog Description   | BSLV216 Industrial Inlets for Surface Mounting, 2P, 16 A, 20 ... 25 V                                                                     |
| Long Description      | Socket Outlet Extra low voltage for surface mounting, rated current 16A, IP44 splashproof, 2-poles, frequency 50-60 Hz, color code Purple |

### Ordering

|                        |               |
|------------------------|---------------|
| E-Number (Sweden)      | E2417761      |
| EAN                    | 7392696009911 |
| Country of Origin      | Austria (AT)  |
| Minimum Order Quantity | 10 piece      |

### Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 71 mm    |
| Product Net Height | 77 mm    |
| Product Net Weight | 0.165 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 108 mm        |
| Package Level 1 Depth / Length | 108 mm        |
| Package Level 1 Height         | 79 mm         |
| Package Level 1 Gross Weight   | 1.65 kg       |
| Package Level 1 EAN            | 7392696010153 |
| Package Level 1 Units          | box 10 piece  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000072M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                      |
|----------------------------|--------------------------------------|
| Additional Information     | 2P                                   |
| Ambient Temperature        | -25 ... 40 °C                        |
| Cable Cross-Section        | 1 ... 10 mm <sup>2</sup>             |
| Cable Diameter             | 8 ... 24 mm                          |
| Color                      | Purple                               |
| Connection Type            | Screw                                |
| Degree of Protection       | IP44                                 |
| Design                     | Surface mounted plug                 |
| Function                   | Extra low voltage wall mounted inlet |
| Housing Material           | Plastic                              |
| Invoice Description        | Ind. P_S#BSLV216                     |
| Number of Poles            | 2                                    |
| Order Multiple             | 10 piece                             |
| Product Main Type          | BSLV                                 |
| Product Name               | Extra low voltage wall mounted inlet |
| Protection Type            | Splashproof                          |
| Rated Current ( $I_n$ )    | 16 A                                 |
| Rated Frequency (f)        | 0...0 Hz                             |
| Rated Voltage ( $U_r$ )    | 20 ... 25 V                          |
| Standards                  | IEC 60309-1, -2                      |
| Suitable for Product Class | IEC Industrial Plugs and Sockets     |
| Instructions and Manuals   | 2CMC700014C0016                      |

|            |                        |
|------------|------------------------|
| RAL Number | RAL 7001 - Silver Grey |
|------------|------------------------|

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets for Extra Low Voltage

