

## PRODUCT-DETAILS

# 232BS9B

Surface inlets, 2P+E, 32 A, 380 ... 415 V



## General Information

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Extended Product Type | 232BS9B                                         |
| Product ID            | 2CMA101061R1000                                 |
| EAN                   | 7392696010610                                   |
| Catalog Description   | Surface inlets, 2P+E, 32 A, 380 ... 415 V       |
| Long Description      | Surface inlets, 2P+E, IP44, 32 A, 380 ... 415 V |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696010610       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                     |                 |
|---------------------|-----------------|
| Product Net Width   | 79 mm           |
| Product Net Height  | 104 mm          |
| Product Net Weight  | 0.27 kg         |
| Mechanical Drawings | 9AKK107680A3027 |

## Container Information

|                                |                         |
|--------------------------------|-------------------------|
| Package Level 1 Width          | 175 mm                  |
| Package Level 1 Depth / Length | 428 mm                  |
| Package Level 1 Height         | 188 mm                  |
| Package Level 1 Gross Weight   | 2.7 kg                  |
| Package Level 1 EAN            | 7392696014557           |
| Package Level 1 Units          | box 10 piece            |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 1100 kg                 |
| Package Level 2 EAN            | 7392696065436           |
| Package Level 2 Units          | pallet (lift) 400 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 2CHC660162X0201 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                      |
|------------------------|----------------------|
| Additional Information | 2P+E                 |
| Ambient Temperature    | -25 ... 40 °C        |
| Cable Cross-Section    | 2.5 ... 10 mm²       |
| Cable Diameter         | 18 mm                |
| Color                  | Red                  |
| Connection Type        | Screw                |
| Cover Color            | Black                |
| Degree of Protection   | IP44                 |
| Design                 | Surface mounted plug |
| Frequency (f)          | 50 Hz<br>60 Hz       |
| Function               | Inlet                |
| Housing Material       | Plastic (PA)         |
| Invoice Description    | IND. P&S#232BS9B     |
| Mounting Holes         | 111x72               |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Number of Poles                 | 3                                |
| Order Multiple                  | 10 piece                         |
| Product Main Type               | EBS                              |
| Product Name                    | Wall mounted inlet               |
| Protection Type                 | Splashproof                      |
| Rated Current (I <sub>n</sub> ) | 32 A                             |
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | 380 ... 415 V                    |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| RAL Number                      | RAL 9005 - Jet Black             |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Inlets

