

PRODUCT-DETAILS

316ERS2W

Wall mounted outlets, 3P+E, 16A, >50 V



General Information

Extended Product Type	316ERS2W
Product ID	2CMA101217R1000
EAN	7392696012171
Catalog Description	Wall mounted outlets, 3P+E, 16A, >50 V
Long Description	Wall mounted outlet, 3P+E, 16A, >50 V Clock Position Of Grounding Contact 2 hour Color code Green

Ordering

EAN	7392696012171
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	89 mm
Product Net Height	117 mm
Product Net Weight	0.27 kg

Container Information

Package Level 1 Width	134 mm
Package Level 1 Depth / Length	177 mm
Package Level 1 Height	467 mm
Package Level 1 Gross Weight	1.35 kg
Package Level 1 EAN	7392696020060
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660168X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616293
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm ²
Cable Diameter	25 mm
Color	Green
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	>300 ... 500 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316ERS2W
Mounting Holes	40x63.5, 40x73.5
Mounting Type	Angled
Number of Poles	4
Order Multiple	5 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Frequency (f)	300 ... 500 Hz
Rated Voltage (U_r)	50 ... 500 V

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications	
eClass	27440510
UNSPSC	39120000

Technical	
Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

