

## PRODUCT-DETAILS

# 416ERS11W

Wall mounted outlets, 3P+N+E, 16A, 250/440 ...  
265/460 V



## General Information

|                       |                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 416ERS11W                                                                                                             |
| Product ID            | 2CMA101233R1000                                                                                                       |
| EAN                   | 7392696012331                                                                                                         |
| Catalog Description   | Wall mounted outlets, 3P+N+E, 16A, 250/440 ... 265/460 V                                                              |
| Long Description      | Wall mounted outlet, 3P+N+E, 16A, 250/440 ... 265/460 V Clock Position Of Grounding<br>Contact 11 hour Color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696012331       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 5 piece             |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 89 mm   |
| Product Net Height | 119 mm  |
| Product Net Weight | 0.30 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 134 mm        |
| Package Level 1 Depth / Length | 177 mm        |
| Package Level 1 Height         | 467 mm        |
| Package Level 1 Gross Weight   | 1.5 kg        |
| Package Level 1 EAN            | 7392696020268 |
| Package Level 1 Units          | box 5 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660168X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1616293         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                         |                       |
|-------------------------|-----------------------|
| Additional Information  | 3P+N+E                |
| Ambient Temperature     | -25 ... 40 °C         |
| Cable Cross-Section     | 1 ... 2.5 mm²         |
| Cable Diameter          | 25 mm                 |
| Color                   | Red                   |
| Connection Type         | Screw                 |
| Degree of Protection    | IP67                  |
| Frequency (f)           | 60 Hz                 |
| Function                | Wall mounted socket   |
| Housing Material        | Plastic (PA)          |
| Invoice Description     | Ind. P&S#416ERS11W    |
| Mounting Holes          | 40x63.5, 40x73.5      |
| Mounting Type           | Angled                |
| Number of Poles         | 5                     |
| Order Multiple          | 5 piece               |
| Product Main Type       | ERS                   |
| Product Name            | Wall mounted socket   |
| Protection Type         | Watertight            |
| Rated Current ( $I_n$ ) | 16 A                  |
| Rated Voltage ( $U_r$ ) | 250/440 ... 265/460 V |
| Recommended Screw       | PH2                   |

|                            |                                  |
|----------------------------|----------------------------------|
| Driver                     |                                  |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| Installation Manual        | 2CMC700014C0016                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

