

PRODUCT-DETAILS

416ERS11W

Wall mounted outlets, 3P+N+E, 16A, 250/440 ...
265/460 V



General Information

Extended Product Type	416ERS11W
Product ID	2CMA101233R1000
EAN	7392696012331
Catalog Description	Wall mounted outlets, 3P+N+E, 16A, 250/440 ... 265/460 V
Long Description	Wall mounted outlet, 3P+N+E, 16A, 250/440 ... 265/460 V Clock Position Of Grounding Contact 11 hour Color code Red

Ordering

EAN	7392696012331
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	89 mm
Product Net Height	119 mm
Product Net Weight	0.30 kg

Container Information

Package Level 1 Width	134 mm
Package Level 1 Depth / Length	177 mm
Package Level 1 Height	467 mm
Package Level 1 Gross Weight	1.5 kg
Package Level 1 EAN	7392696020268
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660168X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616293
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	25 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416ERS11W
Mounting Holes	40x63.5, 40x73.5
Mounting Type	Angled
Number of Poles	5
Order Multiple	5 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Voltage (U_r)	250/440 ... 265/460 V
Recommended Screw	PH2

Driver	
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

