

## PRODUCT-DETAILS

# 232ERS6W

Wall mounted outlets, 2P+E, 32A, 200 ... 250 V



## General Information

|                       |                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 232ERS6W                                                                                                    |
| Product ID            | 2CMA101236R1000                                                                                             |
| EAN                   | 7392696012362                                                                                               |
| Catalog Description   | Wall mounted outlets, 2P+E, 32A, 200 ... 250 V                                                              |
| Long Description      | Wall mounted outlet, 2P+E, 32A, 200 ... 250 V Clock Position Of Grounding Contact 6 hour<br>Color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417631            |
| E-Number (Finland)     | 2420224             |
| E-Number (Norway)      | 1540744             |
| EAN                    | 7392696012362       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 5 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 89 mm  |
| Product Net Height | 117 mm |

|                    |         |
|--------------------|---------|
| Product Net Weight | 0.31 kg |
|--------------------|---------|

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 134 mm        |
| Package Level 1 Depth / Length | 177 mm        |
| Package Level 1 Height         | 467 mm        |
| Package Level 1 Gross Weight   | 1.55 kg       |
| Package Level 1 EAN            | 7392696020336 |
| Package Level 1 Units          | box 5 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660169X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1616295         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                     |
|------------------------|---------------------|
| Additional Information | 2P+E                |
| Ambient Temperature    | -25 ... 40 °C       |
| Cable Cross-Section    | 2.5 ... 6 mm²       |
| Cable Diameter         | 25 mm               |
| Color                  | Blue                |
| Connection Type        | Screw               |
| Degree of Protection   | IP67                |
| Frequency (f)          | 50 Hz<br>60 Hz      |
| Function               | Wall mounted socket |
| Housing Material       | Plastic (PA)        |
| Invoice Description    | Ind. P&S#232ERS6W   |
| Mounting Holes         | 40x63.5, 40x73.5    |
| Mounting Type          | Angled              |
| Number of Poles        | 3                   |
| Order Multiple         | 5 piece             |
| Product Main Type      | ERS                 |
| Product Name           | Wall mounted socket |
| Protection Type        | Watertight          |

|                            |                                  |
|----------------------------|----------------------------------|
| Rated Current ( $I_n$ )    | 32 A                             |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| Installation Manual        | 2CMC700014C0016                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Surface Socket Outlets

