

## PRODUCT-DETAILS

# 216EBU6W

Panel mounted inlets, 2P+E, 16A, 200 ... 250 V



## General Information

|                       |                                                                                                             |
|-----------------------|-------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216EBU6W                                                                                                    |
| Product ID            | 2CMA101259R1000                                                                                             |
| EAN                   | 7392696012591                                                                                               |
| Catalog Description   | Panel mounted inlets, 2P+E, 16A, 200 ... 250 V                                                              |
| Long Description      | Panel mounted inlet, 2P+E, 16A, 200 ... 250 V Clock Position Of Grounding Contact 6 hour<br>Color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| E-Number (Sweden)      | E2417654            |
| E-Number (Finland)     | 2420122             |
| EAN                    | 7392696012591       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 85 mm   |
| Product Net Height | 94 mm   |
| Product Net Weight | 0.11 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 74 mm         |
| Package Level 1 Depth / Length | 187 mm        |
| Package Level 1 Height         | 442 mm        |
| Package Level 1 Gross Weight   | 1.1 kg        |
| Package Level 1 EAN            | 7392696020695 |
| Package Level 1 Units          | box 10 piece  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660170X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1616286         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                        |                           |
|------------------------|---------------------------|
| Additional Information | 2P+E                      |
| Ambient Temperature    | -25 ... 40 °C             |
| Cable Cross-Section    | 1 ... 2.5 mm <sup>2</sup> |
| Cable Diameter         | 6 ... 13 mm               |
| Color                  | Blue                      |
| Connection Type        | Screw                     |
| Degree of Protection   | IP67                      |
| Design                 | Surface mounted plug      |
| Frequency (f)          | 50 Hz<br>60 Hz            |
| Function               | Panel mounted inlet       |
| Housing Material       | Plastic (PA)              |
| Invoice Description    | Ind. P&S#216EBU6W         |
| Mounting Holes         | 75x75                     |
| Mounting Type          | Unified straight flange   |
| Number of Poles        | 3                         |
| Order Multiple         | 10 piece                  |
| Product Main Type      | EBU                       |
| Product Name           | Panel mounted inlet       |
| Protection Type        | Watertight                |

|                            |                                  |
|----------------------------|----------------------------------|
| Rated Current ( $I_n$ )    | 16 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 200 ... 250 V                    |
| Recommended Screw Driver   | PH2                              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals   | 2CMC700014C0016                  |
| RAL Number                 | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 14 ... 12 AWG    |
| Tightening Torque | WireClamp0.8 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

