


PRODUCT-DETAILS

332EBU11W

Panel mounted inlets, 3P+E, 32A, 440 ... 460 V



General Information

Extended Product Type	332EBU11W
Product ID	2CMA101282R1000
EAN	7392696012829
Catalog Description	Panel mounted inlets, 3P+E, 32A, 440 ... 460 V
Long Description	Panel mounted inlet, 3P+E, 32A, 440 ... 460 V Clock Position Of Grounding Contact 11 hour Color code Red

Ordering

EAN	7392696012829
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	85 mm
Product Net Height	91 mm
Product Net Weight	0.18 kg

Container Information

Package Level 1 Width	94 mm
-----------------------	-------

Package Level 1 Depth / Length	192 mm
Package Level 1 Height	442 mm
Package Level 1 Gross Weight	1.8 kg
Package Level 1 EAN	7392696021227
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

CB Certificate	2CHC660171X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616288
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	60 Hz
Function	Panel mounted inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332EBU11W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	EBU
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Frequency (f)	60...60 Hz
Rated Voltage (U _r)	440 ... 460 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications	
eClass	27440519
UNSPSC	39120000

Technical	
Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting
Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

