


## PRODUCT-DETAILS

# 432EBU9W

Panel mounted inlets, 3P+N+E, 32A, 120/208 ...  
144/250 V



## General Information

|                       |                                                                                                                       |
|-----------------------|-----------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 432EBU9W                                                                                                              |
| Product ID            | 2CMA101287R1000                                                                                                       |
| EAN                   | 7392696012874                                                                                                         |
| Catalog Description   | Panel mounted inlets, 3P+N+E, 32A, 120/208 ... 144/250 V                                                              |
| Long Description      | Panel mounted inlet, 3P+N+E, 32A, 120/208 ... 144/250 V Clock Position Of Grounding<br>Contact 9 hour Color code Blue |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696012874       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 10 piece            |

## Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 85 mm   |
| Product Net Height | 91 mm   |
| Product Net Weight | 0.19 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 94 mm         |
| Package Level 1 Depth / Length | 192 mm        |
| Package Level 1 Height         | 442 mm        |
| Package Level 1 Gross Weight   | 1.9 kg        |
| Package Level 1 EAN            | 7392696021326 |
| Package Level 1 Units          | box 10 piece  |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| CB Certificate                 | 2CHC660171X0201 |
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000056M0000 |
| RoHS Information               | 2CMC700005D0001 |
| SEMKO Certificate              | 1616288         |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                         |                         |
|-------------------------|-------------------------|
| Additional Information  | 3P+N+E                  |
| Ambient Temperature     | -25 ... 40 °C           |
| Cable Cross-Section     | 2.5 ... 6 mm²           |
| Cable Diameter          | 13 ... 21.5 mm          |
| Color                   | Blue                    |
| Connection Type         | Screw                   |
| Degree of Protection    | IP67                    |
| Design                  | Surface mounted plug    |
| Frequency (f)           | 50 Hz<br>60 Hz          |
| Function                | Panel mounted inlet     |
| Housing Material        | Plastic (PA)            |
| Invoice Description     | Ind. P&S#432EBU9W       |
| Mounting Holes          | 75x75                   |
| Mounting Type           | Unified straight flange |
| Number of Poles         | 5                       |
| Order Multiple          | 10 piece                |
| Product Main Type       | EBU                     |
| Product Name            | Panel mounted inlet     |
| Protection Type         | Watertight              |
| Rated Current ( $I_n$ ) | 32 A                    |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated Frequency (f)             | 50...60 Hz                       |
| Rated Voltage (U <sub>r</sub> ) | 120/208 ... 144/250 V            |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2                  |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC700014C0016                  |
| RAL Number                      | RAL 7012 - Basalt Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 12 ... 10 AWG    |
| Tightening Torque | WireClamp1.2 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Inlets for Panel Mounting

