

PRODUCT-DETAILS

# 332ERU1W

Panel mounted socket outlets, 3P+E, 32A,  
Optional voltage V



## General Information

Extended Product Type	332ERU1W
Product ID	2CMA101310R1000
EAN	7392696013109
Catalog Description	Panel mounted socket outlets, 3P+E, 32A, Optional voltage V
Long Description	Panel mounted socket outlet, 3P+E, 32A, Optional voltage V Clock Position Of Grounding Contact 1 hour Color code Grey

## Ordering

EAN	7392696013109
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	10 piece

## Dimensions

Product Net Width	85 mm
Product Net Height	98 mm
Product Net Weight	0.23 kg

---

**Container Information**


---

Package Level 1 Width	94 mm
Package Level 1 Depth / Length	192 mm
Package Level 1 Height	442 mm
Package Level 1 Gross Weight	2.3 kg
Package Level 1 EAN	7392696021845
Package Level 1 Units	box 10 piece

---



---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---



---

**Certificates and Declarations (Document Number)**


---

CB Certificate	2CHC660169X0201
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616295
REACH Declaration	2CMC700005D0001

---



---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm <sup>2</sup>
Cable Diameter	13 ... 21.5 mm
Color	Grey
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	AC Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332ERU1W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U <sub>r</sub> )	Optional voltage V

---

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

---

---

## Classifications

---

eClass	27440504
UNSPSC	39120000

---

---

## Technical

---

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

---

---

## Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → Easy & Safe → Socket Outlets for Panel Mounting

