

PRODUCT-DETAILS

416MVS6XW

Industrial Connectors, 3P+N+E, 16A, 200/346 ... 240/415 V



General Information

Extended Product Type	416MVS6XW
Product ID	2CMA101688R1000
EAN	7392696016889
Catalog Description	Industrial Connectors, 3P+N+E, 16A, 200/346 ... 240/415 V
Long Description	Mechanical interlocked socket 16 A, IP 66, 3P+N+E, 200/347...240/415V, 50 and 60Hz, Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 D Ex tD A21 80°C Db

Ordering

EAN	7392696016889
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	115 mm
Product Net Height	181 mm
Product Net Weight	1.450 kg

Container Information

Package Level 1 Width	215 mm
Package Level 1 Depth / Length	165 mm
Package Level 1 Height	335 mm
Package Level 1 Gross Weight	1.45 kg
Package Level 1 EAN	7392696016889
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 55 °C
Cable Diameter	7 ... 17 mm
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion proof Switched interlocked outlet
Housing Material	Glass-fibre reinforced polyester
Invoice Description	Ind. P&S#416MVS6XW
Mounting Type	Vertical
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMVSX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1 IEC 60309-2 IEC 60947-3
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440511
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

