

PRODUCT-DETAILS

463MVS6XW

Industrial Connectors, 3P+N+E, 16A, 200/346 ... 240/415 V



General Information

Extended Product Type	463MVS6XW
Product ID	2CMA101690R1000
EAN	7392696016902
Catalog Description	Industrial Connectors, 3P+N+E, 16A, 200/346 ... 240/415 V
Long Description	Industrial Connectors Explosive proof, 3P+N+E, 63A, 200/346 ... 240/415 V

Ordering

EAN	7392696016902
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	180 mm
Product Net Height	211 mm
Product Net Weight	7.800 kg

Container Information

Package Level 1 Width	260 mm
Package Level 1 Depth / Length	180 mm
Package Level 1 Height	490 mm
Package Level 1 Gross Weight	7.8 kg
Package Level 1 EAN	7392696016902
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-30 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Diameter	16 ... 35 mm
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion proof Switched interlocked outlet
Housing Material	Glass-fibre reinforced polyester
Invoice Description	Ind. P&S#463MVS6XW
Mounting Type	Vertical
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMVSX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I _n)	63 A
Rated Voltage (U _r)	200/346 ... 240/415 V
Standards	IEC 60309-1 IEC 60309-2 IEC 60947-3
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440511
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

