

## PRODUCT-DETAILS

# 4125MVS6XW

## Industrial Plugs, 3P+N+E, 32A, 200/346 ... 240/415 V



### General Information

|                       |                                                                                                                                                                                                  |
|-----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 4125MVS6XW                                                                                                                                                                                       |
| Product ID            | 2CMA101691R1000                                                                                                                                                                                  |
| EAN                   | 7392696016919                                                                                                                                                                                    |
| Catalog Description   | Industrial Plugs, 3P+N+E, 32A, 200/346 ... 240/415 V                                                                                                                                             |
| Long Description      | Mechanical interlocked socket 125 A, IP 66, 3P+N+E, 200/347...240/415V, 50 and 60Hz,<br>Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 D Ex tD<br>A21 80°C Db |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 7392696016919 |
| Country of Origin      | Germany (DE)  |
| Minimum Order Quantity | 1 piece       |

### Dimensions

|                    |           |
|--------------------|-----------|
| Product Net Width  | 270 mm    |
| Product Net Height | 296 mm    |
| Product Net Weight | 21.400 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 555 mm        |
| Package Level 1 Depth / Length | 555 mm        |
| Package Level 1 Height         | 298 mm        |
| Package Level 1 Gross Weight   | 21.4 kg       |
| Package Level 1 EAN            | 7392696016919 |
| Package Level 1 Units          | box 1 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                   |                 |
|-----------------------------------|-----------------|
| Declaration of Conformity<br>- CE | 2CMC700005D0028 |
| Environmental Information         | 2CMC000057M0000 |

## Additional Information

|                          |                                             |
|--------------------------|---------------------------------------------|
| Additional Information   | 3P+N+E                                      |
| Ambient Temperature      | -30 ... 40 °C                               |
| Cable Cross-Section      | 16 ... 70 mm²                               |
| Cable Diameter           | 28 ... 48 mm                                |
| Color                    | Red                                         |
| Connection Type          | Screw Clamp                                 |
| Degree of Protection     | IP66                                        |
| Frequency (f)            | 50 Hz<br>60 Hz                              |
| Function                 | Explosion proof Switched interlocked outlet |
| Housing Material         | Glass-fibre reinforced polyester            |
| Invoice Description      | Ind. P&S#4125MVS6XW                         |
| Mounting Type            | Vertical                                    |
| Number of Poles          | 5                                           |
| Order Multiple           | 1 piece                                     |
| Product Main Type        | CMVSX                                       |
| Product Name             | Switched Interlocked socked outlet EX       |
| Protection Type          | Explosion proof                             |
| Rated Current ( $I_n$ )  | 125 A                                       |
| Rated Voltage ( $U_r$ )  | 200/346 ... 240/415 V                       |
| Standards                | IEC 60309-1<br>IEC 60309-2<br>IEC 60947-3   |
| Instructions and Manuals | 2CMC700014L0201                             |
| RAL Number               | RAL 7001 - Silver Grey                      |

| Classifications |          |
|-----------------|----------|
| eClass          | 27440511 |
| UNSPSC          | 39120000 |

| Categories                                                                                                       |
|------------------------------------------------------------------------------------------------------------------|
| Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX |

