

PRODUCT-DETAILS

4125MVS6XW

Industrial Plugs, 3P+N+E, 32A, 200/346 ... 240/415 V



General Information

Extended Product Type	4125MVS6XW
Product ID	2CMA101691R1000
EAN	7392696016919
Catalog Description	Industrial Plugs, 3P+N+E, 32A, 200/346 ... 240/415 V
Long Description	Mechanical interlocked socket 125 A, IP 66, 3P+N+E, 200/347...240/415V, 50 and 60Hz, Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 D Ex tD A21 80°C Db

Ordering

EAN	7392696016919
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	270 mm
Product Net Height	296 mm
Product Net Weight	21.400 kg

Container Information

Package Level 1 Width	555 mm
Package Level 1 Depth / Length	555 mm
Package Level 1 Height	298 mm
Package Level 1 Gross Weight	21.4 kg
Package Level 1 EAN	7392696016919
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000057M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-30 ... 40 °C
Cable Cross-Section	16 ... 70 mm²
Cable Diameter	28 ... 48 mm
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion proof Switched interlocked outlet
Housing Material	Glass-fibre reinforced polyester
Invoice Description	Ind. P&S#4125MVS6XW
Mounting Type	Vertical
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CMVSX
Product Name	Switched Interlocked socked outlet EX
Protection Type	Explosion proof
Rated Current (I_n)	125 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1 IEC 60309-2 IEC 60947-3
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440511
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

