

PRODUCT-DETAILS

216P6XW

Explosion Proof Plugs, 2P+E, 16 A, 200 ... 250 V



General Information

Extended Product Type	216P6XW
Product ID	2CMA101692R1000
EAN	7392696016926
Catalog Description	Explosion Proof Plugs, 2P+E, 16 A, 200 ... 250 V
Long Description	Plug 16 A, IP 66, 2P+E, 200-250 V, 50 and 60Hz, Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 Ex tD A21 80°C Db

Ordering

EAN	7392696016926
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	76 mm
Product Net Height	76 mm
Product Net Weight	0.420 kg

Container Information

Package Level 1 Width	95 mm
Package Level 1 Depth / Length	95 mm
Package Level 1 Height	189 mm
Package Level 1 Gross Weight	0.42 kg
Package Level 1 EAN	7392696016926
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	2P+E
Ambient Temperature	-40 ... 55 °C
Cable Diameter	8 ... 20 mm
Cable Entry Position	Straight
Color	Blue
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion Proof Plug
Housing Material	Glass-fibre reinforced polyester
Input Voltage (U_{in})	400 V
Invoice Description	Ind. P&S#216P6XW
Number of Poles	3
Order Multiple	1 piece
Product Main Type	CPX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200 ... 250 V
Standards	IEC 60309-1 IEC 60309-2
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 9005 - Jet Black

Classifications	
eClass	27440512
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

