

PRODUCT-DETAILS

416P6XW

Panel mounted socket outlets, 3P+N+E, 16A,
200/346 ... 240/415 V



General Information

Extended Product Type	416P6XW
Product ID	2CMA101693R1000
EAN	7392696016933
Catalog Description	Panel mounted socket outlets, 3P+N+E, 16A, 200/346 ... 240/415 V
Long Description	Panel mounted socket outlets, 3P+N+E, 16A, 200/346 ... 240/415 V Clock Position Of Grounding Contact 6 hour Color code Red

Ordering

EAN	7392696016933
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	92 mm
Product Net Height	92 mm
Product Net Weight	0.430 kg

Container Information

Package Level 1 Width	178 mm
-----------------------	--------

Package Level 1 Depth / Length	178 mm
Package Level 1 Height	94 mm
Package Level 1 Gross Weight	0.430 kg
Package Level 1 EAN	7392696016933
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 55 °C
Cable Diameter	8 ... 18 mm
Cable Entry Position	Straight
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion Proof Plug
Housing Material	Glass-fibre reinforced polyester
Input Voltage (U_{in})	400 V
Invoice Description	Ind. P&S#416P6XW
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CPX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1 IEC 60309-2
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440512
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

