

PRODUCT-DETAILS

432P6XW

Industrial surface inlets, 3P+N+E, 32A, 200/346 ... 240/415 V



General Information

Extended Product Type	432P6XW
Product ID	2CMA101694R1000
EAN	7392696016940
Catalog Description	Industrial surface inlets, 3P+N+E, 32A, 200/346 ... 240/415 V
Long Description	Plug 32 A, IP 66, 3P+N+E, 200/347...240/415V, 50 and 60Hz, Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 Ex tD A21 80°C Db

Ordering

EAN	7392696016940
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	102 mm
Product Net Height	102 mm
Product Net Weight	0.6 kg

Container Information

Package Level 1 Width	114 mm
Package Level 1 Depth / Length	114 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	0.6 kg
Package Level 1 EAN	7392696016940
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-30 ... 55 °C
Cable Diameter	13 ... 28 mm
Cable Entry Position	Straight
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion Proof Plug
Housing Material	Glass-fibre reinforced polyester
Input Voltage (U_{in})	400 V
Invoice Description	Ind. P&S#432P6XW
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CPX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I_n)	32 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1, IEC 60309-2, IEC 60947-3
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440512
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

