

PRODUCT-DETAILS

4125P6XW

Surface outlets, 3P+N+E, 32A, 200/346 ...
240/415 V



General Information

Extended Product Type	4125P6XW
Product ID	2CMA101696R1000
EAN	7392696016964
Catalog Description	Surface outlets, 3P+N+E, 32A, 200/346 ... 240/415 V
Long Description	Plug 125 A, IP 66, 3P+N+E, 200/347 ...240/415V, 50 and 60Hz, Gas explosion protection: II 2 G Ex de IIC T6 Gb, Dust explosion protection: II 2 Ex tD A21 80°C Db

Ordering

EAN	7392696016964
Country of Origin	Germany (DE)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	125 mm
Product Net Height	125 mm
Product Net Weight	1.38 kg

Container Information

Package Level 1 Width	313 mm
Package Level 1 Depth / Length	313 mm
Package Level 1 Height	127 mm
Package Level 1 Gross Weight	1.38 kg
Package Level 1 EAN	7392696016964
Package Level 1 Units	box 1 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0028
Environmental Information	2CMC000073M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 70 °C
Cable Cross-Section	16 ... 70 mm ²
Cable Diameter	30 ... 49 mm
Cable Entry Position	Straight
Color	Red
Connection Type	Screw Clamp
Degree of Protection	IP66
Frequency (f)	50 Hz 60 Hz
Function	Explosion Proof Plug
Housing Material	Glass-fibre reinforced polyester
Input Voltage (U _{in})	400 V
Invoice Description	Ind. P&S#4125P6XW
Number of Poles	5
Order Multiple	1 piece
Product Main Type	CPX
Product Name	ATEX
Protection Type	Explosion proof
Rated Current (I _n)	125 A
Rated Voltage (U _r)	200/346 ... 240/415 V
Standards	IEC 60309-1, IEC 60309-2, IEC 60947-3
Instructions and Manuals	2CMC700014L0201
RAL Number	RAL 7001 - Silver Grey

Classifications	
eClass	27440512
UNSPSC	39120000

Categories
Low Voltage Products and Systems → Industrial Plugs and Sockets → Special Plugs & Sockets → Plugs & Sockets ATEX

