

PRODUCT-DETAILS

216MHS7W

Industrial Switched Interlocked Socket Outlets, 2P+E, 16 A, 480 ... 500 V



General Information

Extended Product Type	216MHS7W
Product ID	2CMA101715R1000
EAN	7392696678001
Catalog Description	Industrial Switched Interlocked Socket Outlets, 2P+E, 16 A, 480 ... 500 V
Long Description	Industrial Switched Interlocked Socket Outlets, 2P+E, IP67, 16 A, 480 ... 500 V

Ordering

E-Number (Sweden)	2416893
EAN	7392696678001
Country of Origin	Czech Republic (CZ)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	168 mm
Product Net Height	114 mm
Product Net Weight	0.7 kg

Container Information

Package Level 1 Width	140 mm
Package Level 1 Depth / Length	200 mm
Package Level 1 Height	135 mm
Package Level 1 Gross Weight	0.7 kg
Package Level 1 EAN	7392696678001
Package Level 1 Units	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	126.4 kg
Package Level 2 EAN	7392696066259
Package Level 2 Units	pallet (lift) 152 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000057M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1515100
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Cable Diameter	6 ... 13 mm
Cable Entry Position	Top and bottom
Cable Outlets Per Side	1xØ25
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#216MHS7W
Mounting Holes	146x91
Mounting Type	Horizontal
Number of Poles	3
Order Multiple	1 piece
Product Main Type	CMHS
Product Name	Switched interlocked outlet
Protection Type	Switched Interlocked

Rated Current (I_n)	16 A
Rated Voltage (U_r)	480 ... 500 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2, -4
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC000032M0001
Installation Manual	2CMC000032M0001
RAL Number	RAL 7001 - Silver Grey

Classifications

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets

