

## PRODUCT-DETAILS

# 463MPR6W

Switched interlocked socket-outlet with RCD, 6h, 30mA, 63A, IP67, 3P+N+E



## General Information

|                       |                                                                                                                                                                               |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 463MPR6W                                                                                                                                                                      |
| Product ID            | 2CMA101934R1000                                                                                                                                                               |
| EAN                   | 7392696019347                                                                                                                                                                 |
| Catalog Description   | Switched interlocked socket-outlet with RCD, 6h, 30mA, 63A, IP67, 3P+N+E                                                                                                      |
| Long Description      | Switched Interlocked Socket Outlet with RCD, earthing sleeve position 6h, 30mA, rated current 63A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

## Ordering

|                        |                     |
|------------------------|---------------------|
| EAN                    | 7392696019347       |
| Country of Origin      | Czech Republic (CZ) |
| Minimum Order Quantity | 1 piece             |

## Dimensions

|                    |        |
|--------------------|--------|
| Product Net Width  | 174 mm |
| Product Net Height | 336 mm |
| Product Net Weight | 1.9 kg |

## Container Information

|                       |        |
|-----------------------|--------|
| Package Level 1 Width | 270 mm |
|-----------------------|--------|

|                                |                        |
|--------------------------------|------------------------|
| Package Level 1 Depth / Length | 490 mm                 |
| Package Level 1 Height         | 210 mm                 |
| Package Level 1 Gross Weight   | 2.030 kg               |
| Package Level 1 EAN            | 7392696679053          |
| Package Level 1 Units          | box 1 piece            |
| Package Level 2 Width          | 800 mm                 |
| Package Level 2 Depth / Length | 1200 mm                |
| Package Level 2 Height         | 900 mm                 |
| Package Level 2 Gross Weight   | 84.96 kg               |
| Package Level 2 EAN            | 7392696066440          |
| Package Level 2 Units          | pallet (lift) 32 piece |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000057M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                                 |                                               |
|---------------------------------|-----------------------------------------------|
| Additional Information          | 3P+N+E                                        |
| Ambient Temperature             | -25 ... 40 °C                                 |
| Cable Cross-Section             | 4 ... 16 mm²                                  |
| Cable Diameter                  | 17 ... 35 mm                                  |
| Cable Entry Position            | Top                                           |
| Cable Outlets Per Side          | 2xØ25                                         |
| Color                           | Red                                           |
| Connection Type                 | Screw                                         |
| Degree of Protection            | IP67                                          |
| Frequency (f)                   | 50 Hz<br>60 Hz                                |
| Function                        | Switched interlocked socket outlet with RCD   |
| Housing Material                | Thermoplastic (PBT)                           |
| Invoice Description             | Ind. P&S#463MPR6W                             |
| Mounting Holes                  | 290x100                                       |
| Mounting Type                   | Vertical                                      |
| Number of Poles                 | 5                                             |
| Number of RCDs 30mA             | 1                                             |
| Number of RCDs                  | 1                                             |
| Order Multiple                  | 1 piece                                       |
| Product Main Type               | CMPR                                          |
| Product Name                    | Industrial Switched Interlocked Socket Outlet |
| Protection Type                 | RCD                                           |
| Rated Current (I <sub>n</sub> ) | 63 A                                          |

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated Residual Current          | 30 mA                            |
| Rated Voltage (U <sub>r</sub> ) | 200/346 ... 240/415 V            |
| Recommended Screw Driver        | PH2                              |
| Standards                       | IEC 60309-1, -2, -4              |
| Suitable for Product Class      | IEC Industrial Plugs and Sockets |
| Instructions and Manuals        | 2CMC000041M0002                  |
| Installation Manual             | 2CMC000041M0002                  |
| RAL Number                      | RAL 7001 - Silver Grey           |

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Critical & Safe → Switched Interlocked Socket Outlets with RCD

