

PRODUCT-DETAILS

216QR6

Ind. P&S#216QR6



General Information

Extended Product Type	216QR6
Product ID	2CMA102289R1000
EAN	7392696022897
Catalog Description	Ind. P&S#216QR6
Long Description	Socket Outlet Panel Mounting, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Blue, Screwless terminals

Ordering

E-Number (Sweden)	E2404976
E-Number (Finland)	2420279
EAN	7392696022897
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	86 mm

Product Net Weight	0.114 kg
--------------------	----------

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.323 kg
Package Level 1 EAN	7392696037655
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm ²
Color	Blue
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216QR6
Mounting Holes	60x60
Number of Poles	3
Order Multiple	10 piece
Product Main Type	QR
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I _N)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	200 ... 250 V

Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 5015 - Sky Blue

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

