


PRODUCT-DETAILS

316QBS6

Ind. P&S#316QBS6



General Information

Extended Product Type	316QBS6
Product ID	2CMA102313R1000
EAN	7392696023139
Catalog Description	Ind. P&S#316QBS6
Long Description	Wall mounted Inlet, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red, Screwless terminals

Ordering

E-Number (Sweden)	E2404999
EAN	7392696023139
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	88 mm
Product Net Height	77 mm
Product Net Weight	0.224 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.303 kg
Package Level 1 EAN	7392696037884
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Color	Red
Connection Type	Screwless
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316QBS6
Mounting Holes	76x48,5
Number of Poles	4
Order Multiple	5 piece
Product Main Type	QBS
Product Name	Wall mounted inlet
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 3002 - Carmine Red

Classifications

eClass	27440519
--------	----------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

