

PRODUCT-DETAILS

316QB6W

Ind. P&S#316QB6W



General Information

Extended Product Type	316QB6W
Product ID	2CMA102321R1000
EAN	7392696023214
Catalog Description	Ind. P&S#316QB6W
Long Description	Panel mounted inlets, earthing sleeve position 6h, 3P+E, 16A, 380 ... 415 V, Screwless terminals, color code red

Ordering

E-Number (Sweden)	E2405006
EAN	7392696023214
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	83 mm
Product Net Height	90 mm
Product Net Weight	0.143 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.613 kg
Package Level 1 EAN	7392696037952
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Red
Connection Type	Screwless
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316QB6W
Mounting Holes	70x76
Number of Poles	4
Order Multiple	10 piece
Product Main Type	QB
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 3002 - Carmine Red

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

