

PRODUCT-DETAILS

416QP6

Ind. P&S#416QP6



General Information

Extended Product Type	416QP6
Product ID	2CMA102324R1000
EAN	7392696023245
Catalog Description	Ind. P&S#416QP6
Long Description	Industrial Plugs, earthing sleeve position 6h, 3P+N+E, IP44, 16 A, 346 ... 415 V, Screwless terminals, color code red

Ordering

E-Number (Sweden)	E2405009
E-Number (Finland)	2420184
E-Number (Norway)	1540777
EAN	7392696023245
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	61 mm
Product Net Height	61 mm
Product Net Weight	0.183 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.013 kg
Package Level 1 EAN	7392696037983
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	6 ... 16 mm
Cable Entry Position	Swivel
Color	Red
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416QP6
Number of Poles	5
Order Multiple	10 piece
Product Main Type	QP
Product Name	Industrial Plug
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

