


PRODUCT-DETAILS

232QP6W

Ind. P&S#232QP6W



General Information

Extended Product Type	232QP6W
Product ID	2CMA102355R1000
EAN	7392696023559
Catalog Description	Ind. P&S#232QP6W
Long Description	Plug, earthing sleeve position 6h, rated current 32A, IP67 watertight, 2-poles+earth, frequency 50-60 Hz, color code Blue, Screwless terminals

Ordering

E-Number (Sweden)	E2405039
EAN	7392696023559
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	93 mm
Product Net Height	93 mm
Product Net Weight	0.229 kg

Container Information

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	2.631 kg
Package Level 1 EAN	7392696038287
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	11 ... 20.5 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232QP6W
Number of Poles	3
Order Multiple	10 piece
Product Main Type	QP
Product Name	Industrial Plug
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Voltage (U_r)	200 ... 250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

