

PRODUCT-DETAILS

332QP6

Ind. P&S#332QP6



General Information

Extended Product Type	332QP6
Product ID	2CMA102364R1000
EAN	7392696023641
Catalog Description	Ind. P&S#332QP6
Long Description	Industrial Plugs, earthing sleeve position 6h, 3P+E, 32A, 380 ... 415 V, Screwless terminals, color code red

Ordering

E-Number (Sweden)	E2405047
EAN	7392696023641
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	63 mm
Product Net Height	63 mm
Product Net Weight	0.201 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.193 kg
Package Level 1 EAN	7392696038362
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1510872
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	11 ... 20.5 mm
Cable Entry Position	Swivel
Color	Red
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332QP6
Number of Poles	4
Order Multiple	10 piece
Product Main Type	QP
Product Name	Industrial Plug
Protection Type	Splashproof
Rated Current (I _n)	32 A
Rated Voltage (U _r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
--------	----------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

