332QRS6W
Ind. P&S#332QRS6W

General Information

Extended Product Type	332QRS6W
Product ID	2CMA102378R1000
EAN	7392696023788
Catalog Description	Ind. P&S#332QRS6W
Long Description	Wall mounted socket-outlet, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red, Screwless terminals

Ordering

E-Number (Sweden)	E2405061
EAN	7392696023788
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	81 mm
Product Net Height	108 mm
Product Net Weight	0.386 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.113 kg
Package Level 1 EAN	7392696038508
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 … 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Color	Red
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332QRS6W
Mounting Holes	75x49
Number of Poles	4
Order Multiple	5 piece
Product Main Type	QRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Voltage (U_r)	380 ... 415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 3002 - Carmine Red

Classifications

eClass	27440510
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe