

PRODUCT-DETAILS

432QRS6

Ind. P&S#432QRS6



General Information

Extended Product Type	432QRS6
Product ID	2CMA102388R1000
EAN	7392696023887
Catalog Description	Ind. P&S#432QRS6
Long Description	Wall mounted socket-outlet, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, Screwless terminals

Ordering

E-Number (Sweden)	E2405070
E-Number (Finland)	2420260
E-Number (Norway)	1540797
EAN	7392696023887
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	88 mm
-------------------	-------

Product Net Height	113 mm
Product Net Weight	0.362 kg

Container Information

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	2.151 kg
Package Level 1 EAN	7392696038591
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Color	Red
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432QRS6
Mounting Holes	84x56
Number of Poles	5
Order Multiple	5 piece
Product Main Type	QRS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I _n)	32 A
Rated Voltage (U _r)	200/346 ... 240/415 V

Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 3002 - Carmine Red

Classifications

eClass	27440510
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

