

PRODUCT-DETAILS

432QC6W

Ind. P&S#432QC6W



General Information

Extended Product Type	432QC6W
Product ID	2CMA102395R1000
EAN	7392696023955
Catalog Description	Ind. P&S#432QC6W
Long Description	Connector, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red, Screwless terminals

Ordering

E-Number (Sweden)	E2405077
EAN	7392696023955
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	109 mm
Product Net Height	109 mm
Product Net Weight	0.316 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.763 kg
Package Level 1 EAN	7392696038669
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	11 ... 20.5 mm
Cable Entry Position	Swivel
Color	Red
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#432QC6W
Number of Poles	5
Order Multiple	5 piece
Product Main Type	QC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	200/346 ... 240/415 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

