

PRODUCT-DETAILS

216QRS4

Ind. P&S#216QRS4



General Information

Extended Product Type	216QRS4
Product ID	2CMA102584R1000
EAN	7392696025843
Catalog Description	Ind. P&S#216QRS4
Long Description	Wall mounted socket-outlet, earthing sleeve position 4h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Yellow, Screwless terminals

Ordering

EAN	7392696025843
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	75 mm
Product Net Height	88 mm
Product Net Weight	0.244 kg

Container Information

Package Level 1 Width	150 mm
-----------------------	--------

Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.403 kg
Package Level 1 EAN	7392696039895
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	Flexible cable 1 ... 2.5 mm ² Rigid cable 1 ... 4 mm ²
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216QRS4
Mounting Holes	64x43
Number of Poles	3
Order Multiple	5 piece
Product Main Type	QRS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I _n)	16 A
Rated Voltage (U _r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440510
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

