

PRODUCT-DETAILS

216QBM4

Ind. P&S#216QBM4



General Information

Extended Product Type	216QBM4
Product ID	2CMA102585R1000
EAN	7392696025850
Catalog Description	Ind. P&S#216QBM4
Long Description	Panel mounted inlets, earthing sleeve position 4h, 2P+E, 16A, 100 ... 130 V, minimized flange, screwless terminals, color code yellow

Ordering

EAN	7392696025850
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	70 mm
Product Net Height	70 mm
Product Net Weight	0.092 kg

Container Information

Package Level 1 Width	150 mm
-----------------------	--------

Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.103 kg
Package Level 1 EAN	7392696039901
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216QBM4
Mounting Holes	56x56
Number of Poles	3
Order Multiple	10 piece
Product Main Type	QBM
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I _N)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U _r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

