

PRODUCT-DETAILS

316QRA4

Ind. P&S#316QRA4



General Information

Extended Product Type	316QRA4
Product ID	2CMA102602R1000
EAN	7392696026024
Catalog Description	Ind. P&S#316QRA4
Long Description	Panel mounted socket outlets, earthing sleeve position 4h, rated current 16A, IP44 splashproof, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Yellow, Screwless terminals

Ordering

EAN	7392696026024
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	83 mm
Product Net Height	119 mm
Product Net Weight	0.157 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.753 kg
Package Level 1 EAN	7392696040068
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316QRA4
Mounting Holes	76x70
Number of Poles	4
Order Multiple	10 piece
Product Main Type	QRA
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 1004 - Golden Yellow

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

