

PRODUCT-DETAILS

316QBA4

Ind. P&S#316QBA4



General Information

Extended Product Type	316QBA4
Product ID	2CMA102605R1000
EAN	7392696026055
Catalog Description	Ind. P&S#316QBA4
Long Description	Panel mounted inlets, unified flange, angled, earthing sleeve position 4h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Yellow, screwless terminals

Ordering

EAN	7392696026055
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	85 mm
Product Net Height	88 mm
Product Net Weight	0.181 kg

Container Information

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	2.151 kg
Package Level 1 EAN	7392696040099
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316QBA4
Mounting Holes	70x70
Number of Poles	4
Order Multiple	10 piece
Product Main Type	QBA
Product Name	Panel mounted inlet
Protection Type	Splashproof
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications

eClass	27440519
--------	----------

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

