

PRODUCT-DETAILS

416QC4

Ind. P&S#416QC4



General Information

Extended Product Type	416QC4
Product ID	2CMA102618R1000
EAN	7392696026185
Catalog Description	Ind. P&S#416QC4
Long Description	Industrial Connectors, earthing sleeve position 4h, 3P+N+E, 16A, 57/100 ... 75/130 V, Screwless terminals, color code yellow

Ordering

EAN	7392696026185
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	87 mm
Product Net Height	87 mm
Product Net Weight	0.228 kg

Container Information

Package Level 1 Width	150 mm
-----------------------	--------

Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	2.463 kg
Package Level 1 EAN	7392696040211
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm²
Cable Diameter	6 ... 16 mm
Cable Entry Position	Swivel
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP44
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#416QC4
Number of Poles	5
Order Multiple	10 piece
Product Main Type	QC
Product Name	Industrial Connector
Protection Type	Splashproof
Rated Current (I _N)	16 A
Rated Voltage (U _r)	57/100 ... 75/130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 7012 - Basalt Grey

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

