

## PRODUCT-DETAILS

# 416QBS4

## Ind. P&S#416QBS4



### General Information

|                       |                                                                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 416QBS4                                                                                                                                                                             |
| Product ID            | 2CMA102626R1000                                                                                                                                                                     |
| EAN                   | 7392696026260                                                                                                                                                                       |
| Catalog Description   | Ind. P&S#416QBS4                                                                                                                                                                    |
| Long Description      | Wall mounted Inlet, earthing sleeve position 4h, rated current 16A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow, screwless terminals, with cover |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 7392696026260 |
| Country of Origin      | Turkey (TR)   |
| Minimum Order Quantity | 5 piece       |

### Dimensions

|                    |          |
|--------------------|----------|
| Product Net Width  | 88 mm    |
| Product Net Height | 84 mm    |
| Product Net Weight | 0.213 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 150 mm        |
| Package Level 1 Depth / Length | 280 mm        |
| Package Level 1 Height         | 225 mm        |
| Package Level 1 Gross Weight   | 1.248 kg      |
| Package Level 1 EAN            | 7392696040297 |
| Package Level 1 Units          | box 5 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000072M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Additional Information     | 3P+N+E                           |
| Ambient Temperature        | -25 ... 40 °C                    |
| Cable Cross-Section        | 1 ... 2.5 mm²                    |
| Color                      | Yellow                           |
| Connection Type            | Screwless                        |
| Degree of Protection       | IP44                             |
| Design                     | Surface mounted plug             |
| Frequency (f)              | 50 Hz<br>60 Hz                   |
| Function                   | Inlet                            |
| Housing Material           | Plastic (PA)                     |
| Invoice Description        | Ind. P&S#416QBS4                 |
| Mounting Holes             | 76x48,5                          |
| Number of Poles            | 5                                |
| Order Multiple             | 5 piece                          |
| Product Main Type          | QBS                              |
| Product Name               | Wall mounted inlet               |
| Protection Type            | Splashproof                      |
| Rated Current ( $I_n$ )    | 16 A                             |
| Rated Frequency (f)        | 50...60 Hz                       |
| Rated Voltage ( $U_r$ )    | 57/100 ... 75/130 V              |
| Standards                  | IEC 60309-1, -2                  |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |

|                          |                          |
|--------------------------|--------------------------|
| Instructions and Manuals | 2CMC700014C0016          |
| RAL Number               | RAL 1004 - Golden Yellow |

Classifications

|        |          |
|--------|----------|
| eClass | 27440519 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

