

PRODUCT-DETAILS

332QC4W

Ind. P&S#332QC4W



General Information

Extended Product Type	332QC4W
Product ID	2CMA102701R1000
EAN	7392696027014
Catalog Description	Ind. P&S#332QC4W
Long Description	Connector, earthing sleeve position 4h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Yellow, Screwless terminals

Ordering

EAN	7392696027014
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

Dimensions

Product Net Width	102 mm
Product Net Height	102 mm
Product Net Weight	0.3 kg

Container Information

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	1.841 kg
Package Level 1 EAN	7392696040693
Package Level 1 Units	box 5 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm²
Cable Diameter	11 ... 20.5 mm
Cable Entry Position	Swivel
Color	Yellow
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332QC4W
Number of Poles	4
Order Multiple	5 piece
Product Main Type	QC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I_n)	32 A
Rated Voltage (U_r)	100 ... 130 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number	RAL 7012 - Basalt Grey
------------	------------------------

Classifications

eClass	27440509
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

