

PRODUCT-DETAILS

432QBA4 Ind. P&S#432QBA4



General Information	
Extended Product Type	432QBA4
Product ID	2CMA102717R1000
EAN	7392696027175
Catalog Description	Ind. P&S#432QBA4
Long Description	Panel mounted inlets, unified flange, angled, earthing sleeve position 4h, rated current 32A, IP44 splashproof, 3-poles+neutral+earth, frequency 50-60 Hz, color code Yellow, screwless terminals
Ordering	
EAN	7392696027175
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece
Dimensions	
Product Net Width	85 mm
Product Net Height	102 mm
Product Net Weight	0.476 kg

IEC 60309-1, -2

Standards

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	5.101 kg
Package Level 1 EAN	7392696040846
Package Level 1 Units	box 10 piece
Environmental	
RoHS Status	Following EU Directive 2011/65/EU
Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001
Additional Information	
Additional Information	
Ambient Temperature	-25 40 °C
Ambient Temperature Cable Cross-Section	-25 40 °C 2.5 10 mm
Ambient Temperature Cable Cross-Section Color	-25 40 °C 2.5 10 mm Yellow
Ambient Temperature Cable Cross-Section Color Connection Type	-25 40 °C 2.5 10 mm ² Yellow Screwless
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection	-25 40 °C 2.5 10 mm² Yellow Screwless IP44
Ambient Temperature Cable Cross-Section Color Connection Type	-25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design	-25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f)	-25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function	-25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA)
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description	-25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inlet Plastic (PA) Ind. P&S#432QBA4
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inter Plastic (PA) Ind. P&S#432QBA4
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA) Ind. P&S#432QBA4 70×70 anglec
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type Number of Poles	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA) Ind. P&S#432QBA4 70x70 anglec
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type Number of Poles Order Multiple	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA) Ind. P&S#432QBA4 70x70 anglec 510 piece
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type Number of Poles Order Multiple Product Main Type	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA) Ind. P&S#432QBA4 70x70 anglec 50 Hz 10 piece
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type Number of Poles Order Multiple Product Main Type Product Name	-25 40 °C 2.5 10 mm Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inle Plastic (PA) Ind. P&S#432QBA4 70x70 angled 510 piece QBA Panel mounted inle Splashproor
Ambient Temperature Cable Cross-Section Color Connection Type Degree of Protection Design Frequency (f) Function Housing Material Invoice Description Mounting Holes Mounting Type Number of Poles Order Multiple Product Main Type Product Name Protection Type	3P+N+E -25 40 °C 2.5 10 mm² Yellow Screwless IP44 Surface mounted plug 50 Hz 60 Hz Inlet Plastic (PA) Ind. P&S#432QBA4 70x70 angled 510 piece QBA Panel mounted inlet Splashproof 32 A 5060 Hz

Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 1004 - Golden Yellow

Classifications	
eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems \rightarrow Industrial Plugs and Sockets \rightarrow Fast & Safe

