

## PRODUCT-DETAILS

# 216QRS9

## Ind. P&S#216QRS9



### General Information

|                       |                                                                                                                                                                      |
|-----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Extended Product Type | 216QRS9                                                                                                                                                              |
| Product ID            | 2CMA102863R1000                                                                                                                                                      |
| EAN                   | 7392696028639                                                                                                                                                        |
| Catalog Description   | Ind. P&S#216QRS9                                                                                                                                                     |
| Long Description      | Wall mounted socket-outlet, earthing sleeve position 9h, rated current 16A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Red, Screwless terminals |

### Ordering

|                        |               |
|------------------------|---------------|
| EAN                    | 7392696028639 |
| Country of Origin      | Turkey (TR)   |
| Minimum Order Quantity | 5 piece       |

### Dimensions

|                    |         |
|--------------------|---------|
| Product Net Width  | 75 mm   |
| Product Net Height | 88 mm   |
| Product Net Weight | 0.25 kg |

## Container Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 150 mm        |
| Package Level 1 Depth / Length | 280 mm        |
| Package Level 1 Height         | 225 mm        |
| Package Level 1 Gross Weight   | 1.433 kg      |
| Package Level 1 EAN            | 7392696042079 |
| Package Level 1 Units          | box 5 piece   |

## Environmental

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificates and Declarations (Document Number)

|                                |                 |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 2CMC700005D0001 |
| Environmental Information      | 2CMC000072M0000 |
| RoHS Information               | 2CMC700005D0001 |
| REACH Declaration              | 2CMC700005D0001 |

## Additional Information

|                            |                                                         |
|----------------------------|---------------------------------------------------------|
| Additional Information     | 2P+E                                                    |
| Ambient Temperature        | -25 ... 40 °C                                           |
| Cable Cross-Section        | Flexible cable 1 ... 2.5 mm²<br>Rigid cable 1 ... 4 mm² |
| Color                      | Red                                                     |
| Connection Type            | Screwless                                               |
| Degree of Protection       | IP44                                                    |
| Frequency (f)              | 50 Hz<br>60 Hz                                          |
| Function                   | Outlet                                                  |
| Housing Material           | Plastic (PA)                                            |
| Invoice Description        | Ind. P&S#216QRS9                                        |
| Mounting Holes             | 64x43                                                   |
| Number of Poles            | 3                                                       |
| Order Multiple             | 5 piece                                                 |
| Product Main Type          | QRS                                                     |
| Product Name               | Wall mounted socket                                     |
| Protection Type            | Splashproof                                             |
| Rated Current ( $I_n$ )    | 16 A                                                    |
| Rated Voltage ( $U_r$ )    | 380 ... 415 V                                           |
| Standards                  | IEC 60309-1, -2                                         |
| Suitable for Product Class | IEC Industrial Plugs and Sockets                        |
| Instructions and Manuals   | 2CMC700014C0016                                         |

|            |                        |
|------------|------------------------|
| RAL Number | RAL 3002 - Carmine Red |
|------------|------------------------|

Classifications

|        |          |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

