

PRODUCT-DETAILS

316QR9W

Ind. P&S#316QR9W



General Information

Extended Product Type	316QR9W
Product ID	2CMA102889R1000
EAN	7392696028899
Catalog Description	Ind. P&S#316QR9W
Long Description	Panel mounted socket outlets, earthing sleeve position 9h, 3P+E, rated current 16A, 200 ... 250 V, unified flange, color code Blue, Screwless terminals

Ordering

EAN	7392696028899
Country of Origin	Turkey (TR)
Minimum Order Quantity	10 piece

Dimensions

Product Net Width	75 mm
Product Net Height	114 mm
Product Net Weight	0.13 kg

Container Information

Package Level 1 Width	150 mm
Package Level 1 Depth / Length	280 mm
Package Level 1 Height	225 mm
Package Level 1 Gross Weight	1.483 kg
Package Level 1 EAN	7392696042321
Package Level 1 Units	box 10 piece

Environmental

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Additional Information

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1.5 ... 4 mm²
Color	Blue
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Outlet
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#316QR9W
Mounting Holes	60x60
Number of Poles	4
Order Multiple	10 piece
Product Main Type	QR
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I_n)	16 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	200 ... 250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 5015 - Sky Blue

Classifications

eClass	27440504
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

