

PRODUCT-DETAILS

MC-S5/200 400V-6h

Ind. P&S#MC-S5/200 400V-6h



General Information

Extended Product Type	MC-S5/200 400V-6h
Product ID	2CMA103145R1000
EAN	7392696031455
Catalog Description	Ind. P&S#MC-S5/200 400V-6h
Long Description	Industrial plugs, 3P+N+E, IP67, 200 A, 200/346 ... 240/415 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature.

Ordering

EAN	7392696031455
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	142 mm
Product Net Height	134 mm
Product Net Weight	2.9 kg

Container Information

Package Level 1 Width	407 mm
Package Level 1 Depth / Length	407 mm
Package Level 1 Height	187 mm
Package Level 1 Gross Weight	2.9 kg
Package Level 1 EAN	7392696031455
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 100 °C
Cable Cross-Section	35 ... 150 mm²
Cable Diameter	45 ... 66 mm
Cable Entry Position	Anti-kink sleeve
Color	Red
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic
Invoice Description	Ind. P&S#MC-S5/200 400V-6h
Number of Poles	5
Order Multiple	1 piece
Product Main Type	MC
Product Name	High current male connector
Protection Type	Watertight
Rated Current (I_n)	200 A
Rated Voltage (U_r)	200/346 ... 240/415 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9005 - Jet Black

Classifications

eClass	27440509
--------	----------

UNSPSC

39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

