

PRODUCT-DETAILS

MCP-S5/250 230V-9h

Ind. P&S#MCP-S5/250 230V-9h



General Information

Extended Product Type	MCP-S5/250 230V-9h
Product ID	2CMA103194R1000
EAN	7392696031943
Catalog Description	Ind. P&S#MCP-S5/250 230V-9h
Long Description	Panel mounted inlet, 3P+N+E, IP67, 250 A, 200/346 ... 240/415 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature.

Ordering

EAN	7392696031943
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Dimensions

Product Net Width	204 mm
Product Net Height	140 mm
Product Net Weight	2.4 kg

Container Information

Package Level 1 Width	288 mm
Package Level 1 Depth / Length	288 mm
Package Level 1 Height	142 mm
Package Level 1 Gross Weight	2.4 kg
Package Level 1 EAN	7392696031943
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)

Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information

Additional Information	3P+N+E
Ambient Temperature	-40 ... 100 °C
Cable Diameter	45 ... 66 mm
Color	Blue
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Plastic
Invoice Description	Ind. P&S#MCP-S5/250 230V-9h
Mounting Holes	120x120
Number of Poles	5
Order Multiple	1 piece
Product Main Type	MCP
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I_n)	250 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	120/208 ... 144/250 V
Standards	IEC 60309-1, -2
Sub-Function	C-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9007 - Grey Aluminium

Classifications

eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

