

8.1 kg

PRODUCT-DETAILS

MCP-S4/250 690V-5h Ind. P&S#MCP-S4/250 690V-5h



Product Net Weight

General Information	
Extended Product Type	MCP-S4/250 690V-5h
Product ID	2CMA103202R1000
EAN	7392696032025
Catalog Description	Ind. P&S#MCP-S4/250 690V-5h
Long Description	Panel mounted inlet, 3P+E, IP67, 250 A, 200/346 240/415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connecors also suitable for marine applications. Aluminum housing. Designed for high temperature.
Ordering	
EAN	7392696032025
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece
Dimensions	
Product Net Width	230 mm
Product Net Height	350 mm

MCP-S4/250 690V-5h 2

277 mr	Package Level 1 Width
277 mr	Package Level 1 Depth / Length
352 mr	Package Level 1 Height
8.1 k	Package Level 1 Gross Weight
739269603202	Package Level 1 EAN
box 1 piece	Package Level 1 Units
umber)	Certificates and Declarations (Document Number)
NoDecNe	Declaration of Conformity - CE
2CMC000074M0000	Environmental Information
	Additional Information
3P+E	Additional Information
-40 100 °C	Ambient Temperature
45 66 mr	Cable Diameter
Blac	Color
Scree	Connection Type
IP6	Degree of Protection
Surface mounted plu	Design
50 H 60 H	Frequency (f)
Inle	Function
Aluminur	Housing Material
Ind. P&S#MCP-S4/250 690V-5	Invoice Description
155x15	Mounting Holes
	Number of Poles
1 piec	Order Multiple
MC	Product Main Type
Panel mounted inle	Product Name
Watertigh	Protection Type
250	Rated Current (I _n)
5060 H	Rated Frequency (f)
600 690	Rated Voltage (U _r)
IEC 60309-1, -	Standards
	Sub-Function
B-lin	Suitable for Product Class
B-lin IEC Industrial Plugs and Socket 2CMC700014C001	Instructions and Manuals

Classifications	
eClass	27440519
UNSPSC	39120000

MCP-S4/250 690V-5h 3

Categories

Low Voltage Products and Systems \rightarrow Industrial Plugs and Sockets \rightarrow High Current Connectors >125A

