

350 mm

PRODUCT-DETAILS

MCP-S4/400 230V-9h Ind. P&S#MCP-S4/400 230V-9h



Product Net Height

Extended Product Type	MCP-S4/400 230V-9h
Product ID	2CMA103209R1000
EAN	7392696032094
Catalog Description	Ind. P&S#MCP-S4/400 230V-9h
Long Description	Panel mounted inlet, 3P+E, IP67, 400 A, 200/346 240/415 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connecors also suitable for marine applications. Aluminum housing. Designed for high temperature.
Ordering	
Ordering EAN	7392696032094
	7392696032094 Switzerland (CH)
EAN	
EAN Country of Origin	Switzerland (CH)
EAN Country of Origin	Switzerland (CH)

Product Net Weight 8.1 kg

Container Information	
Package Level 1 Width	277 mm
Package Level 1 Depth / Length	277 mm
Package Level 1 Height	352 mm
Package Level 1 Gross Weight	8.1 kg
Package Level 1 EAN	7392696032094
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information	
Additional Information	3P+E
Ambient Temperature	-40 100 °C
Color	Blue
Connection Type	Screw
Degree of Protection	IP67
Design	Surface mounted plug
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#MCP-S4/400 230V-9h
Mounting Holes	155x155
Number of Poles	4
Order Multiple	1 piece
Product Main Type	MCP
Product Name	Panel mounted inlet
Protection Type	Watertight
Rated Current (I _n)	400 A
Rated Frequency (f)	5060 Hz
Rated Voltage (U _r)	200250 V
Standards	IEC 60309-1, -2
Sub-Function Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9007 - Grey Aluminium

MCP-S4/400 230V-9h 3

Classifications	
eClass	27440519
UNSPSC	39120000

Categories

Low Voltage Products and Systems \rightarrow Industrial Plugs and Sockets \rightarrow High Current Connectors >125A

