

240 mm

242 mm

PRODUCT-DETAILS

Dimensions
Product Net Width

Product Net Height

## MCW-S5/400 500V-7h Ind. P&S#MCW-S5/400 500V-7h



General Information	
Extended Product Type	MCW-S5/400 500V-7h
Product ID	2CMA103296R1000
EAN	7392696032964
Catalog Description	Ind. P&S#MCW-S5/400 500V-7h
Long Description	Surface mounted inlet, 3P+N+E, IP67, 400 A, 500 V, The robust B-Line connectors are ideal for applications (tunneling, mining), where high mechanical loads may arise. Furthermore, numerous options, such as the saltwater-resistant housing, make the connecors also suitable for marine applications. Aluminum housing. Designed for high temperature.
Ordering	
EAN	7392696032964
Country of Origin	Switzerland (CH)
Minimum Order Quantity	1 piece

Product Net Weight 10.5 kg

Container Information	
Package Level 1 Width	464 mm
Package Level 1 Depth / Length	464 mm
Package Level 1 Height	244 mm
Package Level 1 Gross Weight	10.5 kg
Package Level 1 EAN	7392696032964
Package Level 1 Units	box 1 piece

Certificates and Declarations (Document Number)	
Declaration of Conformity - CE	NoDecNee
Environmental Information	2CMC000074M0000

Additional Information	
Additional Information	3P+N+E
Ambient Temperature	-40 100 °C
Cable Diameter	45 65 mm
Cable Entry Position	Anti-kink sleeve
Color	Black
Connection Type	Screw
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Inlet
Housing Material	Aluminum
Invoice Description	Ind. P&S#MCW-S5/400 500V-7h
Mounting Holes	140x140
Number of Poles	5
Order Multiple	1 piece
Product Main Type	MCW
Product Name	Wall mounted inlet
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	400 A
Rated Voltage (U <sub>r</sub> )	480 500 V
Standards	IEC 60309-1, -2
Sub-Function Sub-Function	B-line
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016
RAL Number	RAL 9007 - Grey Aluminium

Classifications	
eClass	27440509
UNSPSC	39120000

## Categories

Low Voltage Products and Systems  $\rightarrow$  Industrial Plugs and Sockets  $\rightarrow$  High Current Connectors >125A

