
PRODUCT-DETAILS

FC-S5/200 400V-6h

Ind. P&S#FC-S5/200 400V-6h



General Information

| | |
|-----------------------|--|
| Extended Product Type | FC-S5/200 400V-6h |
| Product ID | 2CMA103305R1000 |
| EAN | 7392696033053 |
| Catalog Description | Ind. P&S#FC-S5/200 400V-6h |
| Long Description | Industrial connectors, 3P+N+E, IP67, 200 A, 200 ... 250 V, The compact C-Line connectors have a robust plastic housing and are perfect for applications with limited space conditions as well as for certain industries (chemistry, food industry). Designed for high temperature. |

Ordering

| | |
|------------------------|------------------|
| EAN | 7392696033053 |
| Country of Origin | Switzerland (CH) |
| Minimum Order Quantity | 1 piece |

Dimensions

| | |
|--------------------|--------|
| Product Net Width | 190 mm |
| Product Net Height | 185 mm |
| Product Net Weight | 3.6 kg |

Container Information

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 407 mm |
| Package Level 1 Depth / Length | 407 mm |
| Package Level 1 Height | 187 mm |
| Package Level 1 Gross Weight | 3.6 kg |
| Package Level 1 EAN | 7392696033053 |
| Package Level 1 Units | box 1 piece |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | NoDecNee |
| Environmental Information | 2CMC000074M0000 |

Additional Information

| | |
|----------------------------|----------------------------------|
| Additional Information | 3P+N+E |
| Ambient Temperature | -40 ... 100 °C |
| Cable Diameter | 45 ... 65 mm |
| Cable Entry Position | Anti-kink sleeve |
| Color | Red |
| Connection Type | Screw |
| Degree of Protection | IP67 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Connector |
| Housing Material | Plastic |
| Invoice Description | Ind. P&S#FC-S5/200 400V-6h |
| Number of Poles | 5 |
| Order Multiple | 1 piece |
| Product Main Type | FC |
| Product Name | High current connector |
| Protection Type | Splashproof |
| Rated Current (I_n) | 200 A |
| Rated Voltage (U_r) | 200/346 ... 240/415 V |
| Standards | IEC 60309-1, -2 |
| Sub-Function | C-line |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instructions and Manuals | 2CMC700014C0016 |
| RAL Number | RAL 9005 - Jet Black |

Classifications

| | |
|--------|----------|
| eClass | 27440509 |
| UNSPSC | 39120000 |

Categories

Low Voltage Products and Systems → Industrial Plugs and Sockets → High Current Connectors >125A

